

you will have the freedom to choose the robot corresponding to your actual needs for greater efficiency and economic benefits. All SF MIMETIC series are equipped with LIKEPRECISION technology, the ultra-precise RV Precision Gearbox, which enables the robot to take full

Applications

ြာင	
Handling	





Glazing

advantage of its advantages even at high operating speeds.













Spraying

Picking/Packing Stamping

12Kg J6 Distance between centres of rotation 156 (mm) 250 200 300 L₁₅ (mm) J5 Distance between centres of rotation


SF20-C2150 Wrist load torque chart

Note: The centre of gravity point of the load should be within the wrist torque diagram when in use

SF20-C2150 Data Overview


Model		SF20-C2150
Structure		Vertically Articulated
Number of Axis		6
Radius		2150mm
Payload		20kg
Repeatability		±0.06mm
Drive Mode		AC Servo Motor
Maximum Speed	J1 J2 J3 J4 J5 J6	140° /s 140° /s 140° /s 350° /s 230° /s 250° /s
Range of Motion	J1 J2 J3 J4 J5 J6	±170° +100° /-157° +95° /-80° ±180° ±125°/-125° ±720°
Allowable Moment	J4 J5 J6	42N.M 42N.M 23N.M
Allowable Inertia	J4 J5 J6	1.26kg.m2 1.26kg.m2 0.49kg.m2
Protection Rating		IP 65
	Temp.	0-45°C
Operating	Humidity	Below 95%RH
Conditions	Vibration	Below 4.9m/s2
	Other	Eliminate Signal Noise
Base Size		396*396mm
Height		1618.5mm
Weight		246KG
Mounting Positions		Any angle
Power Consumption		3.8kVA

SF20-C2150 Range of Motion






External & Installation Dimensions



A-Way Diagram (End Flange Mounting Dimensions)



B-Way Fiagram (Base Mounting Dimensions)



44